

EP-10

Piston clamp MAXI-R



Mod Maxi R	61020	20 cm	16 cm	14 cm	3,19
	61030	30 cm	16 cm	14 cm	3,50
	61040	40 cm	16 cm	14 cm	3,82
	61050	50 cm	16 cm	14 cm	4,13
	61060	60 cm	16 cm	14 cm	4,45
	61080	80 cm	16 cm	14 cm	5,07
	61100	100 cm	16 cm	14 cm	5,70
	61120	120 cm	16 cm	14 cm	6,33
	61140	140 cm	16 cm	14 cm	6,96
	61150	150 cm	16 cm	14 cm	7,27
	61160	160 cm	16 cm	14 cm	7,59
	61180	180 cm	16 cm	14 cm	8,21
	61200	200 cm	16 cm	14 cm	8,83
	61220	220 cm	16 cm	14 cm	9,46
	61250	250 cm	16 cm	14 cm	10,09
	61300	300 cm	16 cm	14 cm	10,72

Mod. Maxi R **Llanta / bar** 40 mm x 10 mm

Fuerza Máxima
Maximum pressure 10000 N

Main features:

- Rolled spring steel bar which gives maximum pressure held throughout the whole job.
- Nodular cast iron jaws
- Covered double threaded screw which doubles both the pressure and the speed with a greasing hole for optimum lubrication and a new dismantable, interchangeable new easy grip handle.
- The surface of the fixed jaw is grooved to achieve maximum grip on angled pieces, tubes, etc
- The moving jaw is kept firmly in position thanks to the spring activated brake at the back.

Materials and Finishing:

All raw materials without exception used in Ind. Piqueras tools come from countries within the European Union. This guarantees maximum quality and permits easy and full control.

FOUNDRY WORK	<p>-Malleable Grey: EN-GJMW 400-5 quality under EN1567 rule. Finishing, thermal decarburising treatment, shot blasting, phosphating and electrostatic RAL 3004 red colour epoxy polyester painting.</p> <p>-Nodular cast iron: EN-GJS-400-15 quality under UNE-En 1563 ruling. Stabilising heat treated, shot blasted, phosphated and electrostatic RAL 3004 red colour epoxy polyester painted Guaranteed tracking realised using the alphanumerical codes embossed on all pieces throughout their whole productive life--casting date and number and its place in the tooling.</p>
BAR	<p>-40x10 mm bar -DIN C-60 quality (90 Kg/m² pressure) heat rolled. -Shot blasting finish giving stability and cleanliness. -Single coat rust-proof dark grey painting finish. -All pieces are packed and labelled with date and number and stored in our warehouses until used permitting full tracking</p>
BRAKE	<p>Anti-slip tempered steel on moving jaw Stop to prevent loss</p>
HANDLE	<p>Nylon and fibreglass</p>
SCREWS	<p>White zinc coated steel without Hexavalent-Chromium</p>

The cast iron pieces used in our tools easily and clearly pass all kinds of tests on hardness, resistance and elasticity.

All the pieces carry a casting date and number which make all quality controls easier and allow a complete tracking of the piece. The careful design also guarantees optimum mechanical performance.

Packing and labelling:

In packets of two and five bound with plastic bands and cling film wrapped.
Individually coded label EAN-13

RULES:

No special safety rulings applied

All work carried out following ISO:9001 and ISO :14001 rules